

MATERIALS ON STOCK

Innerlayers:

Panasonic R-1755V (Tg 170°C)

0.1 mm 18/18; 35/35
0.15 mm 18/18; 35/35
0.2 mm 18/18; 35/35; 70/70
0.3 mm 18/18; 35/35
0.36 mm 18/18; 35/35; 70/70
0.46 mm 18/18; 35/35
0.51 mm 18/18; 35/35
0.71 mm 18/18; 35/35; 70/70
1.08 mm 18/18; 35/35; 70/70
1.2 mm 18/18; 35/35

Prepregs:

Panasonic R1650V (Tg 170°C)

0.063 mm 1080
0.110 mm 2116
0.180 mm 7628

Please bear in mind that copper 70μ or thicker needs at least 0.2mm prepreg next to it, so double prepregs must be used.

Rigid (for single- and doublesided boards only):

Panasonic MC 100 (Tg135°C)

0.8 mm 18/18; 35/35
1.0 mm 18/18; 35/35
1.2 mm 18/18; 35/35
1.6 mm 18/18; 35/35; 70/70;105/105
2.0 mm 18/18; 35/35;
2.4 mm 18/18; 35/35; 70/70

Rigid (for single- and doublesided boards only):

Panasonic MC 100 (Tg170°C)

1.60 mm 18/18; 35/35; 70/70; 105/105

RF materials:

Rogers RO4003C

0.203 mm 18/18
0.508 mm 18/18
0,813 mm 18/18