



Ver M, Nov 22nd, 2018

MATERIALS ON STOCK

Innerlayers:

Panasonic R-1755V (Tg 170°C)

0.1 mm 18/18; 35/35
0.15 mm 18/18; 35/35
0.2 mm 18/18; 35/35
0.3 mm 18/18; 35/35
0.36 mm 18/18; 35/35; 70/70
0.46 mm 18/18; 35/35
0.51 mm 18/18; 35/35
0.71 mm 18/18; 35/35; 70/70
1.08 mm 18/18; 35/35; 70/70
1.2 mm 18/18; 35/35

Prepregs:

Panasonic R1650V (Tg 170°C)

0.063 mm 1080
0.110 mm 2116
0.180 mm 7628

Please bear in mind that copper 70 μ or thicker needs at least 0.2mm prepreg next to it, so double prepregs must be used.

Rigid (for single- and doublesided boards only):

Panasonic MC 100 (Tg135°C)

0.8 mm 18/18; 35/35
1.0 mm 18/18; 35/35
1.2 mm 18/18; 35/35
1.6 mm 18/18; 35/35; 70/70;105/105
2.0 mm 18/18; 35/35;
2.4 mm 18/18; 35/35; 70/70

Rigid (for single- and doublesided boards only):

Panasonic MC 100 (Tg170°C)

1.60 mm 18/18; 35/35; 70/70; 105/105

RF materials:

Rogers RO4003C

0.203 mm 18/18
0.508 mm 18/18
0,813 mm 18/18